



DTH Products

[Our Company](#)
[DTH Products](#)
[News](#)
[Project](#)
[Summaries](#)
[Tech Support](#)
[Contact Us](#)
[Web Specials!](#)
[Associations](#)
[Home](#)

BIT SPECIFICATIONS

FOR METRIC CONVERSION				
BIT SPECIFICATIONS				
CONVENTIONAL				
Hammer	Bit Shank	Bit Range (in.)	Weight (lbs.)	Face Design
Patriot 35A	C35/3.5	3-1/2 to 4-1/8	14 - 15	Flat, Convex
Patriot 40	340A	4-1/4 to 5-1/8	18 - 21	Flat, Concave, Convex
Champion 40	340A	4-1/4 to 5-1/8	18 - 21	Flat, Concave, Convex
DCS5	QL50	5-1/2 to 6-1/8	33 - 36	Flat, Concave, Convex
Patriot 50	QL50	5-1/2 to 6-1/8	33 - 36	Flat, Concave, Convex
DCS6	QL60	6 to 8-1/2	48 - 68	Flat, Concave, Convex
Patriot 60W	360	6 to 8-1/2	52 - 72	Flat, Concave, Convex
Patriot 60WQ	QL60	6 to 8-1/2	48 - 68	Flat, Concave, Convex
Challenger 6	360	6 to 8-1/2	52 - 72	Flat, Concave, Convex
Patriot 80	380	7-7/8 to 10	100 - 125	Flat, Concave
Challenger 80	380	7-7/8 to 10	100 - 125	Flat, Concave
Challenger 80Q	QL80	7-7/8 to 10	100 - 125	Flat, Concave
Challenger 100	N100	9-7/8 to 15	210 - 377	Flat, Concave
Patriot 120	N120	11-7/8 to 17-1/2	384 - 571	Flat, Concave
Challenger 120	N120	11-7/8 to 17-1/2	384 - 571	Flat, Concave
Patriot 125	N125	12-1/4 to 20	433 - 779	Flat, Concave
Challenger 125	N125	12-1/4 to 20	433 - 779	Flat, Concave